

Reliable back-up power for energy storage systems

The Static Transfer Switch (STS) enables precise control of inverters, allowing seamless transitions between grid-connected and off-grid modes. In the event of a grid outage, the inverter switches to off-grid mode, providing power to critical loads through solar panels or batteries. When grid power is restored, the inverter smoothly transitions back to grid-connected operation. The STS is versatile, supporting connections with generators and accommodating large loads such as heat pumps and high-power motors. This robust solution ensures continuous and reliable power supply, offering flexibility and efficiency in energy management.



Compatible with hybrid inverter ET50



Facilitates back-up power



Supports integration with generators



Technical Data		STS200-80-10
Electrical Data		
Nominal Output Voltage (V)	380 / 400, 3L / N / PE	
Output Voltage Range (V)	176 ~ 276	
Nominal AC Frequency (Hz)	50 / 60	
AC Frequency Range (Hz)	45 ~ 65	
Inverter Side Data		
Nominal Apparent Power(VA)	50000	
Max. Apparent Power (VA) ^{*1}	50000	
Nominal Current (A) ^{*5}	72.5	
Max. Current (A) ^{*2*6}	75.8	
Grid Side Data		
Nominal Apparent Power (VA)	50000	
Max. Apparent Power (VA) ^{*3}	50000	
Nominal Current (A) ^{*5}	72.5	
Max. Current (A) ^{*4*6}	75.8	
Back-up Side Data		
Nominal Apparent Power (VA)	50000	
Max. Apparent Power without Grid (VA)	55000	
Max. Apparent Power with Grid (VA)	138000	
Nominal Current (A) ^{*5}	72.5	
Max. Current (A) ^{*4*7}	83.3	
Generator / PV inverter Side Data		
Nominal Apparent Power (VA)	50000	
Max. Apparent Power (VA)	55000	
Nominal Current (A) ^{*5}	72.5	
Max. Current (A) ^{*7}	83.3	
Other Electrical Data		
Nominal Current of AC Side Relay (A)	200	
Nominal Current of Generator Side Relay (A)	90	
Switch Time (ms)	<10	
General Data		
Operating Temperature Range (°C)	-35 ~ +60	
Max. Operating Altitude (m)	4000	
Cooling Method	Nature Convection	
Communication with Inverter	RS485	
Weight (kg)	16.5	
Dimension (W × H × D mm)	510 × 425 × 156	
Topology	Non-isolated	
Mounting Method	Wall Mounted	
Ingress Protection Rating	IP65	
Certification		
Safety Regulation	IEC62109-1/-2	
EMC	EN61000-6-1, EN61000-6-2, EN61000-6-3, EN61000-6-4	

*1: When the inverter is operating in the off-grid state, Max. Apparent Power of Inverter Side can be reached 55kW.

*2: When the inverter is operating in the off-grid state, Max. Current of Inverter Side can be reached 83.3A.

*3: Max. Input Power at grid port (purchased power) 138kW.

*4: Max purchases current of gid side and back up side can be reached at 200A.

*5: When Nominal Output Voltage is 380V, the Nominal Current is 75.8A.

*6: When Nominal Output Voltage is 400V, the Max. Current is 72.5A.

*7: When Nominal Output Voltage is 400V, the Max. Current is 79.7A.

*: Please visit GoodWe website for the latest certificates.