

Smart Meter

GoodWe's single-phase Smart Meter is an energy meter designed for real-time power monitoring, enabling load tracking and export power management. When combined with GoodWe's SEMS monitoring platform, it provides comprehensive insights into residential energy usage. Its compact and high-precision design simplifies installation and operation, offering accurate data and seamless compatibility with residential energy solutions.



Export power limit & load monitoring



120A CTs included



Accuracy Class 1.0



Slim 19mm width for easy installation

Model	GMK110	GMK110D
Measuring range		
Support Grid Type	1P2W	
Operating Voltage (Vac)*	85 ~ 288	
Frequency (Hz)	50 / 60	
Current Transformer Ratio	120A: 40mA	
Number of Current Transformers	1	2
Accuracy		
Voltage / Current	Class 1	
Active Energy	Class 1	
Reactive Energy	Class 2	
Communication		
Communication Method	RS485	
Communication Distance (m)	1000	
General		
Dimensions (W x H x D mm)	19 x 85 x 67	
Housing	1 module	
Weight	50	
Mounting	DIN rail	
User Interface	2 LED	
Power Consumption (W)	≤5	
Environment		
Ingress Protection Rating	IP20	
Operating Temperature Range (°C)	-30 ~ +60	
Storage Temperature Range (°C)	-30 ~ +70	
Relative Humidity (non-condensing)	0 ~ 95%	
Max. Operating Altitude (m)	3000	

*: Supports input voltage up to 1.1Un.

*: The integrated meter CT has been unified to 120A: 40mA, and the previous 200A: 50mA will be phased out after June 2026.

*: Please visit GoodWe website for the latest certificates.

*: All pictures shown are for reference only. Actual appearance may vary.